



COMPRESSORS

INTERNATIONAL

TECHNICAL INFORMATION SHEET SCR250H

Direct drive 380V/415V/440V 50Hz/3 Phase	BAR	7	8	10	12.5
Effective volume flow (ISO 1217/Annex C)	m³/min	39	38.5	34	29
Terminal power (ISO 1217/Annex C)	kW	214	225	219	225
Drive Motor					
Nominal motor rating	kW	185			
Motor type		TEFC			
Full load current /380V	A	352	377	363	379
Full load current /415V	A	334	358	345	360
Full load current /440V	A	322	345	333	347
Starting current	A	Approx.2.5times full load current			
Motor output at shaft	kW	196	207	201	208
Motor Input at no-load	kW	65	68	66	68
Motor enclosure/IP		IP54			
Motor speed	RPM	1485			
Frequency range	Hz	50			
Motor efficiency	%	95.8	95.8	95.8	95.8
Service factor		1.3	1.3	1.3	1.3
Cooling					
Type of cooling		Air-Cooled			
Cooling air volume	m³/h	40000			
Cooling water flow at 32 °C	m³/h				
Water Pressure Max./Min	bar				
Water Connection In/Out					
Air End					
Compression Stage		2			
Temperatures					
Ambient temperature range	°C	1-45			
Dimensions/Weights/General data					
Compressed air outlet		DN100			
L x W x H	mm	3400*2200*2100			
Weight	kg	6200			
Oil capacity	L	160			
Residual oil content	mg/m³	≤3			
Noise level at 1 meter	dB(A)	84±3			
Outlet temperature	°C	≤ Environment temp +10			