



COMPRESSORS

INTERNATIONAL

TECHNICAL INFORMATION SHEET SCR375H

Direct drive 380V/6kV/10kV 50Hz/3 Phase	BAR	7	8	10	12.5
Effective volume flow (ISO 1217/Annex C)	m³/min	60	56	51	46
Terminal power (ISO 1217/Annex C)	kW	347	358	326	341
Drive Motor					
Nominal motor rating	kW	280			
Motor type		TEFC			
Full load current /380V	A	511	572	501	550
Full load current /6kV		33	37	30	35
Full load current /10kV		20	22	19	21
Starting current	A	Approx.2.5times full load current			
Motor output at shaft	kW	320	329	302	317
Motor Input at no-load	kW	105	108	98	102
Motor enclosure/IP		IP54			
Motor speed	RPM	1485			
Frequency range	Hz	50			
Motor efficiency	%	96	96	96	96
Service factor		1.3	1.3	1.3	1.3
Cooling					
Type of cooling		Air-Cooled			
Cooling air volume	m³/h	52500			
Cooling water flow at 32°C	m³/h				
Water Pressure Max./Min	bar				
Water Connection In/Out					
Air End					
Compression Stage		2			
Temperatures					
Ambient temperature range	°C	1-45			
Dimensions/Weights/General data					
Compressed air outlet		DN125			
L x W x H	mm	4000*2000*2300			
Weight 380V/6kV/10kV	kg	8200/9000/9500			
Oil capacity	L	242			
Residual oil content	mg/m³	≤3			
Noise level at 1 meter	dB(A)	86±3			
Outlet temperature	°C	≤ Environment temp +10			